



## Prodin Ferrite S.L.

Polígono Industrial "Molí dels Frares" Calle C/A - Nave 2

08620 Sant Vicenç dels Horts - Barcelona - España

T: +34 936 724 610

info@prodinferrite.com - www.prodinferrite.com

### CARACTERÍSTICAS HILO TRIPLEX

Conductor diametro (mm)	Tolerancia (mm)	Diametro total (mm)	Diametro máximo (mm)	Tensión ruptura (V)	Resistencia ( $\Omega$ /km)	Metros por bobina
0.20	$\pm 0.008$	0.360 ~ 0.380 ~ 0.400	0.420	6000	607.6	6000
0.22	$\pm 0.008$	0.380 ~ 0.400 ~ 0.420	0.440	6000	498.4	6000
0.25	$\pm 0.008$	0.410 ~ 0.430 ~ 0.450	0.470	6000	382.5	6000
0.27	$\pm 0.010$	0.430 ~ 0.450 ~ 0.470	0.490	6000	331.4	5000
0.30	$\pm 0.010$	0.460 ~ 0.480 ~ 0.505	0.540	6500	262.9	5000
0.32	$\pm 0.010$	0.480 ~ 0.500 ~ 0.525	0.560	6500	230.0	5000
0.35	$\pm 0.010$	0.510 ~ 0.530 ~ 0.555	0.590	6500	191.2	5000
0.37	$\pm 0.010$	0.530 ~ 0.550 ~ 0.575	0.610	6500	191,2	5000
0.40	$\pm 0.010$	0.575 ~ 0.600 ~ 0.625	0.660	7000	145,3	5000
0.45	$\pm 0.010$	0.625 ~ 0.650 ~ 0.675	0.710	7000	114,2	5000
0.50	$\pm 0.010$	0.680 ~ 0.700 ~ 0.725	0.760	7000	91,43	4000
0.55	$\pm 0.020$	0.720 ~ 0.750 ~ 0.780	0.810	7000	78,15	4000
0.60	$\pm 0.020$	0.770 ~ 0.800 ~ 0.830	0.860	7000	65,26	3000
0.65	$\pm 0.020$	0.820 ~ 0.850 ~ 0.880	0.910	7000	55,31	3000
0.70	$\pm 0.020$	0.870 ~ 0.900 ~ 0.930	0.960	7000	47,47	3000
0.75	$\pm 0.020$	0.920 ~ 0.950 ~ 0.980	1.010	7000	41,19	3000
0.80	$\pm 0.020$	0.970 ~ 1.000 ~ 1.030	1.060	7000	26,08	3000
0.85	$\pm 0.020$	1.020 ~ 1.050 ~ 1.080	1.110	7000	31,87	2000
0.90	$\pm 0.020$	1.070 ~ 1.100 ~ 1.130	1.160	7000	28,35	2000
0.95	$\pm 0.020$	1.120 ~ 1.150 ~ 1.180	1.210	7000	25,38	2000
1.00	$\pm 0.030$	1.170 ~ 1.200 ~ 1.230	1.260	7000	23,33	2000