



# PRODUCT DATA APPROVAL SHEET

Core- I10025A

Cosmo Ferrites Ltd.

**Appearance & Shape:** To be free from any defect such as flow, burrs, unevenness etc, As per IEC standards. **Effective Parameters irrespective of material grade**

Approximate weight (without Gap): 300g/Pc



## I10025A (OL)



Material	Initial Permeability ( $\mu_{iac}$ )	AL Value (nH)	$\mu_e$ Approx.	$P_v$ (W/set)
CF139	2100 $\pm$ 20%	NA	NA	NA
CF297	2300 $\pm$ 20%	NA	NA	NA
CF292	1800 $\pm$ 20%	NA	NA	NA

Note: All faces will be ground.

## Dimensions

Dimension	Nominal (in mm)	Maximum (in mm)	Minimum (in mm)
A	101.5	103.5	99.5
F	24.9	25.6	24.2
G	24.9	25.6	24.2

For Cosmo Ferrites Limited-INDIA  
Checked By: A.K.  
Approved By: B.S.



Authorized By: KSR  
Date: 15-01-2013



## Prodin Ferrite S.L.

Calle A, 27, 08620 Sant Vicenç dels Horts, Barcelona (Spain)

Tel.: +34 93 672 46 10

[info@prodinferrite.com](mailto:info@prodinferrite.com)

[www.prodinferrite.com](http://www.prodinferrite.com)