

Appearance & Shape: To be free from any defect such as flow, burrs, unevenness etc, As per IEC standards.

Effective Parameters irrespective of material grade (per set)

- Effective Length (L_e): 52.0mm
- Effective Area (A_e): 202.0mm²
- Effective Area (A_{Min}): 202.0mm²
- Effective Volume (V_e): 10600mm³

Approximate weight (without Gap): 55g/Set



P3622 gapped (AL)

Test Conditions: 1 KHz/300mV/N=100/25°C

Material	Initial Permeability (μ_{iac})	AL Value (nH)/Set	μ_e Approx./Set	
CF139	2100 ±20%	132±5%	-	
CF139	2100 ±20%	250±5%	-	
CF139	2100 ±20%	400±5%	-	
CF139	2100 ±20%	1000±5%	-	
CF255	5500 ±20%	132±5%	-	
CF255	5500 ±20%	250±5%	-	
CF255	5500 ±20%	400±5%	-	
CF255	5500 ±20%	1000±5%	-	

Dimensions:

Dimension	Nominal (in mm)	Maximum (in mm)	Minimum (in mm)
Groove(G)	5.2	5.6	4.8
a	26.2	26.8	25.6
d1	35.5	36.0	35.0
d2	30.5	30.9	30.1
d3	15.9	16.2	15.6
d4	5.5	5.62	5.38
h1	10.85	11.05	10.65
h2	7.6	7.75	7.45

