



# PRODUCT DATA APPROVAL SHEET

Core- UU10130

Cosmo Ferrites Ltd. - INDIA

Appearance & Shape: To be free from any defect such as flow, burrs, unevenness etc, As per IEC standards.  
Effective Parameters irrespective of material grade (per set)

- Effective Length ( $L_e$ ): 368.0mm
- Effective Area ( $A_e$ ): 840.0mm<sup>2</sup>
- Effective Area ( $A_{min}$ ): 826.1mm<sup>2</sup>
- Effective Volume ( $V_e$ ): 310800mm<sup>3</sup>

Approximate weight (without Gap): 1500gm/Set




## UU10130 Un-gapped (OL)

Test Conditions: 1 KHz/300mV/N=100/Lo=Zero/25°C

Material	Initial Permeability ( $\mu_{iac}$ )	AL Value (nH)	$\mu_e$ Approx.	Pv (W/set)
CF139	2100 ±20%	5600 +30%/-20%	≈1960	<31.0(100mT,100kHz, 100°C)
CF297	2300 ±20%	6100 +30%/-20%	≈2140	<24.8(100mT,100kHz, 100°C)

Dimension	Nominal (in mm)	Maximum (in mm)	Minimum (in mm)
A	101.9	102.8	101.0
B	-	-	45.0
C	76.0	76.5	75.5
D	48.0	48.9	47.1
E	30.0	30.6	29.4

Dimensions :



For Cosmo Ferrites  
Limited-INDIA



**Prodin Ferrite S.L.**

Calle A, 27, 08620 Sant Vicenç dels Horts, Barcelona (Spain)

Tel.: +34 93 672 46 10

[info@prodinferrite.com](mailto:info@prodinferrite.com) [www.prodinferrite.com](http://www.prodinferrite.com)