


Appearance & Shape: To be free from any defect such as flow, burrs, unevenness etc, As per IEC standards.

Effective Parameters irrespective of material grade (per set)

- Effective Length (L_e): 66.4mm
- Effective Area (A_e): 113.2mm²
- Effective Area (A_{Min}): 110.5mm²
- Effective Volume (V_e): 7516mm³

Approximate Weight (without Gap): 37g/Set



EE3213 Un-gapped

Test Conditions: 1KHz/150mV/CFR COIL,N=100/25°C

| Material Grade | Initial Permeability (μ_{iac}) | AL Value (nH)/Set | P_V (W/set) | Ordering code |
|----------------|--------------------------------------|-------------------|----------------------------------|---------------|
| CF295 | 3000 \pm 20% | 4100 +30%/-20% | ≤ 0.90 (100mT,100kHz,100°C) | CF295 EE3213 |

Dimensions:

| Dimension | Nominal (in mm) | Maximum (in mm) | Minimum (in mm) |
|-----------|-----------------|-----------------|-----------------|
| A | 31.9 | 32.9 | 30.9 |
| B | 22.77 | 23.54 | 22.0 |
| C | 14.0 | 14.4 | 13.6 |
| D | 9.65 | 9.9 | 9.4 |
| E | 8.9 | 9.15 | 8.65 |
| F | 12.7 | 13.0 | 12.4 |

